



typ závitů A
do dřeva, oceli do 3,0 mm a hliníku

TECHNICKÉ PARAMETRY a CENA:

rozměry v mm	svěrná tloušťka	šrouby bez podl.			šrouby s podl.		
		bal.	Kč/100 ks	skl.	bal.	Kč/100 ks	skl.
E16							
6.5 x 20		500	240	✓	500	390	✓
6.5 x 25		500	290	✓	500	440	✓
6.5 x 32		500	390		500	540	
6.5 x 38		500	440		500	590	✓
6.5 x 45		500	490		500	640	✓
6.5 x 50		500	540		500	690	✓
6.5 x 65		500	640		500	790	✓
6.5 x 75		500	740		500	890	✓
6.5 x 90		500	840	✓	250	990	✓
6.5 x 100		250	940		250	1 090	✓
6.5 x 115		250	1 040	✓	250	1 190	✓
6.5 x 125		250	1 140	✓	250	1 290	✓
6.5 x 150		250	1 240	✓	250	1 390	✓
6.5 x 175		250	1 540	✓	250	1 690	
6.5 x 200		250	1 840	✓	100	1 990	✓

Doporučené průměry předvrtání do oceli

Celková tloušťka	Průměr vrtáku
0,63 - 0,75	4,0
0,88 - 1,25	4,5
1,50 - 2,00	5,0
2,00 - 3,00	5,7